



HMG Coatings (South) Ltd
 Faraday Park
 West Portway Ind Est
 Andover
 Hants
 SP10 3SA
Tel: 01264 356296
Fax: 01264 338123

PAINTS

PRODUCT NAME**SYNERGY® TURBOTHANE**

Material Safety Datasheet

1. Identification of the substance/mixture and of the company/undertaking

Product: SYNERGY® TURBOTHANE
Limitations of Use: For Industrial and Professional use only.
Company: **HMG COATINGS SOUTH LTD**
 Faraday Park
 West Portway Ind Est
 Andover
 Hants
 SP10 3SA

Telephone: 01264 356296
Fax: 01264 338123
Web: www.hmgcoatings.com

2. Hazards identification**Classification of the substance or mixture**

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.



Xi; Irritant

R38: Irritating to skin.

R10: Flammable.

- Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

1330-20-7	Xylene (mix)
100-41-4	ethylbenzene

- Label elements**

- Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- Code letter and hazard designation of product:**

Xn Harmful

- Hazard-determining components of labelling:**

Xylene (mix)

- Risk phrases:**

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

38 Irritating to skin.

- Safety phrases:**

9 Keep container in a well-ventilated place.

23 Do not breathe fumes/vapour/spray

25 Avoid contact with eyes.

36/37 Wear suitable protective clothing and gloves.

43 In case of fire, use water or powdered extinguishing agent.

60 This material and its container must be disposed of as hazardous waste.

- Other hazards**

- Results of PBT and vPvB assessment**

- PBT:** Not applicable.

- vPvB:** Not applicable.



HMG Coatings (South) Ltd
 Faraday Park
 West Portway Ind Est
 Andover
 Hants
 SP10 3SA
 Tel: 01264 356296
 Fax: 01264 338123

PRODUCT NAME

SYNERGY® TURBOTHANE

3. Composition/Information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7	Xylene (mix)	Xn R20/21; Xi R38 R10	10-25%
CAS: 123-86-4 EINECS: 204-658-1	Butyl ethanoate	R10-66-67	10-25%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene	Xn R20; F R11	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate	Xi R36 R10	2.5-10%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4. First aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5. Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

6. Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.



HMG Coatings (South) Ltd
 Faraday Park
 West Portway Ind Est
 Andover
 Hants
 SP10 3SA
 Tel: 01264 356296
 Fax: 01264 338123

PRODUCT NAME

SYNERGY® TURBOTHANE

7. Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Keep receptacles tightly sealed.
 Ensure good ventilation/extraction at the workplace.
 Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8. Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

123-86-4 Butyl ethanoate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

Ingredients with biological limit values:

1330-20-7 Xylene (mix)

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Respiratory protection:** When spraying the product, use a respiratory protective device.



HMG Coatings (South) Ltd
 Faraday Park
 West Portway Ind Est
 Andover
 Hants
 SP10 3SA
 Tel: 01264 356296
 Fax: 01264 338123

PAINTS

PRODUCT NAME

SYNERGY® TURBOTHANE

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9. Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 78 °C

· **Flash point:** 26 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.1 Vol %

Upper: 10.4 Vol %

· **Vapour pressure at 20 °C:** 10.7 hPa

· **Density at 20 °C:** 0.938 g/cm³



HMG Coatings (South) Ltd
 Faraday Park
 West Portway Ind Est
 Andover
 Hants
 SP10 3SA
Tel: 01264 356296
Fax: 01264 338123

PAINTS

PRODUCT NAME**SYNERGY® TURBOTHANE**

- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with water:** NOT MISCIBLE
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
- Dynamic:** Not determined.
- Kinematic:** Not determined.
- **Solvent content:**
- Organic solvents:** 51.4 %
- Solids content:** 28.0 %
- **Other information** No further relevant information available.

10. Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11. Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values relevant for classification:		
1330-20-7 Xylene (mix)		
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

· LD/LC50 values relevant for classification:		
1330-20-7 Xylene (mix)		
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful
 Irritant

Continued on next page



HMG Coatings (South) Ltd
 Faraday Park
 West Portway Ind Est
 Andover
 Hants
 SP10 3SA
 Tel: 01264 356296
 Fax: 01264 338123

PRODUCT NAME

SYNERGY® TURBOTHANE

12. Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13. Disposal considerations

- **Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14. Transport information

UN-Number

- **ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **ADR** 1263 PAINT (not viscous)
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids.
- **Label** 3
- **Packing group**
- **ADR, IMDG, IATA** III
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Flammable liquids.
- **Danger code (Kemler):** 30
- **EMS Number:** F-E,S-E
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **ADR**
- **Limited quantities (LQ)** 5L
- **Transport category** 3
- **Tunnel restriction code** D/E



PAINTS

HMG Coatings (South) Ltd
 Faraday Park
 West Portway Ind Est
 Andover
 Hants
 SP10 3SA
 Tel: 01264 356296
 Fax: 01264 338123

PRODUCT NAME**SYNERGY® TURBOTHANE****15. Regulatory information (Supply and Labelling)**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**
- **Technical instructions (air):**

Class	Share in %
NK	51.4

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16. Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

R20/21 Harmful by inhalation and in contact with skin.

R36 Irritating to eyes.

R38 Irritating to skin.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:** Product safety department: LABORATORY

- **Contact:** Health & Safety Officer